This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

THE BRITISH LIBRARY SCIENCE REFERENCE AND IMPORMATION SERVICE



WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



i

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

C03C 13/00

A1

(11) International Publication Number: WO 95/31411

(43) International Publication Date: 23 November 1995 (23.11.95)

DE

(21) International Application Number: PCT/EP95/01843

(22) International Filing Date: 16 May 1995 (16.05.95)

(30) Priority Data:
P 44 17 231.1 17 May 1994 (17.05.94) DE

1 February 1995 (01.02.95)

(71) Applicant (for all designated States except US): ISOVER SAINT-GOBAIN [FR/FR]; Les Miroirs, 18, avenue d'Alsace, F-92400 Courbeyoie (FR).

(72) Inventors; and

195 03 172.5

(75) Inventors/Applicants (for US only): LOHE, Peter [DE/DE]; Ritterstrasse 5, D-67112 Mutterstadt (DE). HOLSTEIN, Wolfgang [DE/DE]; Herderstrasse 2, D-35315 Homberg (DE). SCHWAB, Wolfgang [DE/DE]; Schönauer Strasse 25, D-68723 Plankstadt (DE).


(74) Agent: KADOR & PARTNER; Corneliusstrasse 15, D-80469 Munich (DE).

(81) Designated States: AU, BR, CA, CN, CZ, FI, HU, JP, KR, NO, NZ, PL, SI, SK, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

(54) Title: A MINERAL-FIBER COMPOSITION



(57) Abstract

A biologically degradable mineral-fiber composition characterized by the following constituents in percent by weight: SiO₂ 50 to 65, Al₂O₃ less than 2, CaO 16 to 30, MgO 4 to 15, Na₂O 8 to 20, K₂O 0 to 2, B₂O₃ 0 to 10, TiO₂, Fe₂O₃, Cr₂O₃, BaO, MnO, P₂O₅ 0 to 5.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
ΑU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	LI	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Larvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Denmark	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	US	United States of America
FI	Finland	ML	Mali	UZ	Uzbekistan
FR	France	MN	Mongolia	VN	Viet Nam
GA	Gabon		-		

PCT/EP95/01843

A mineral-fiber composition

The present invention relates to a mineral-fiber composition that is biologically degradable.

The prior art describes some mineral-fiber compositions which are said to be biologically degradable.

The biological degradability of mineral-fiber compositions is of great importance because various studies point out that mineral fibers with very small diameters in the range of less than 3 microns are suspected to be carcinogenic, while biologically degradable mineral fibers of such dimensions show lower or no carcinogenicity.

However not only the biological degradability is of crucial importance but also the mechanical and thermal properties of the mineral fibers, or the products produced therefrom, and the processibility of the mineral-fiber composition. For example mineral fibers are used to a great extent for insulation purposes. In particular for this application in the industrial area sufficient temperature stability of the mineral fibers is necessary.

Also, the mineral-fiber composition must permit processibility by known methods for producing mineral fibers with a small diameter, for example the jet process.

The invention is based on the problem of providing a novel mineral-fiber composition that is characterized by biological degradability, has good temperature stability and is easy to process.

The invention is based on the finding that this problem can be solved by a mineral-fiber composition that is built up substantially from silicon oxide, calcium oxide, magnesium oxide and sodium oxide.

It has turned out that such a mineral-fiber composition fulfills the combination of the necessary properties, namely biological degradability, temperature stability and good processibility.

1

The object of the invention is a mineral-fiber_composition that is biologically degradable, characterized by the following constituents in percent by weight:

SiO ₂	50	to 65
Al ₂ O ₃	les	s than 2
CaO	16	to 30
MgO	4	to 15
Na ₂ O	8	to 20
K ₂ O	0	to 2
B ₂ O ₃	0	to 10
TiO ₂ , Fe ₂ O ₃ , Cr ₂ O ₃ , BaO, MnO, P ₂ O ₅	0	to 5

The inventive mineral-fiber compositions are drawable by the jet process or the rotary process. The obtained fibers have good temperature stability. Surprisingly enough, the mineral-fiber compositions show biological degradability. The mean fiber diameter is preferably 10 microns or less, and especially between 2.5 and 5 microns.

The inventive mineral-fiber compositions preferably have the following constituents in percent by weight:

SiO ₂	55	to 60
Al ₂ O ₃	less	than 1.5
CaO	16	to 25
MgO	5	to 15
Na ₂ O	9	to 15
K ₂ O	less	than 2
B ₂ O ₃	0	to 8
TiO ₂ , Fe ₂ O ₃ , Cr ₂ O ₃ , BaO, MnO, P ₂ O ₅	0	to 5

In particular, the inventive mineral-fiber compositions have the following constituents in percent by weight:

SiO ₂	55	to 59
Al ₂ O ₃	less	than 1.5
CaO	18	to 23
MgO	8	to 12
Na ₂ O	9	to 13
K ₂ O	less	than 1
B ₂ O ₃ .	0	to 3
TiO ₂ , Fe ₂ O ₃ , Cr ₂ O ₃ , BaO, MnO, P ₂ O ₅	0	to 3

The content of magnesium oxide is preferably 6 to 12 percent by weight and in particular 8 to 12 percent by weight.

The content of chromium oxide is preferably less than 1.5 percent by weight and in particular less than 1.0 percent by weight.

The content of boron oxide is preferably less than 4 percent by weight.

To assess biological degradability the standard powder test of the German Glass Society was used. This is an easily conducted method and gives a sufficient measure of biological degradability. The method is described in L. Springer, "Laboratoriumsbuch für die Glasindustrie", 3rd edition, 1950, Halle/S: W. Knapp Verlag.

The temperature behavior of the mineral fibers was determined by the Swedish method. In this method a silit tube furnace is used with a horizontal working tube open on both sides having a length of 350 mm and an inside diameter of 27 mm. In the center of the furnace there is a small ceramic supporting plate (30 X 20 X 3 mm) for holding the test sample. The test sample has dimensions of 12 X 12 X 12 mm or 12 mm ¢ X 12 mm height. The bulk density is normally 100 kg/m³. The temperature increase is 5 K/min. The change in test sample height is determined continuously with a reading optic.

The invention shall be described in more detail in the following with reference to examples.

Example 1

A mineral wool of the following composition in percent by weight was produced:

SiO ₂	56
Al ₂ O ₃	0.5
CaO	20
MgO	10
Na ₂ O	10
B_2O_3	2.7

This composition could be processed well to mineral fibers with a mean diameter of 2.5 microns by the jet process at a drawing temperature of 1330°C.

An investigation according to the standard powder test of the German Glass Society yielded a value of 35 mg/kg and thus a value for high biological degradability.

Determination of temperature behavior by the Swedish method yielded a temperature stability at 5% reduction in height of 620°C, which can be clearly seen from the corresponding diagram shown by way of example in the single drawing.

Example 2

A mineral wool with the following composition in percent by weight was produced:

	% by weight	Mole %
SiO ₂	56	52.75
Al ₂ O ₃	1.0	0.55
CaO	21	21.20
MgO	11	15.45
Na ₂ O	11	10.05

This composition could be processed well to mineral fibers with a mean diameter of 2.7 microns by the jet process at a drawing temperature of 1310°C.

An investigation according to the standard powder test of the German Glass Society yielded a value of 37 mg/kg and thus a value for high biological degradability.

Determination of temperature behavior by the Swedish method yielded a temperature stability at 5% reduction in height of 600°C.

Claims

1. A mineral-fiber composition that is biologically degradable, characterized by the following constituents in percent by weight:

SiO ₂	50	to 65
Al ₂ O ₃	less t	han 2
CaO	16	to 30
MgO	4	to 15
Na ₂ O	8	to 20
K ₂ O	0	to 2
B ₂ O ₃	0	to 10
TiO ₂ , Fe ₂ O ₃ , Cr ₂ O ₃ , BaO, MnO, P ₂ O ₅	0	to 5

2. The mineral-fiber composition of claim 1, characterized by the following constituents in percent by weight:

SiO ₂	55	to 60
Al ₂ O ₃	less t	han 1.5
CaO	16	to 25
MgO	5	to 15
Na ₂ O .	9	to 15
K ₂ O	less t	han 2
B ₂ O ₃	0	to 8
TiO ₂ , Fe ₂ O ₃ , Cr ₂ O ₃ , BaO, MnO, P ₂ O ₅	0	to 5


3. The mineral-fiber composition of claim 1, characterized by the following constituents in percent by weight:

SiO₂ 55 to 59

Al ₂ O ₃	less 1	than 1.5
CaO	18	to 23
MgO	8	to 12
Na ₂ O	9	to 13
K ₂ O	less t	han 1
B ₂ O ₃	0	to 3
TiO ₂ , Fe ₂ O ₃ , Cr ₂ O ₃ , BaO, MnO, P ₂ O ₅	0	to 3

^{4.} The mineral-fiber composition of any of claims 1 to 3, characterized in that the content of boron oxide is less than 4 percent by weight.





INTERNATIONAL SEARCH REPORT

Inten , al Application No PCT/FP 95/01843

		1	FUI/EF 33	/01043
A. CLASS IPC 6	SIFICATION OF SUBJECT MATTER C03C13/00			
According	to International Patent Classification (IPC) or to both national cl	assification and IPC		
B. FIELD	S SEARCHED			
Minimum o	documentation scarched (classification system followed by classification could be compared to the country of th	ication symbols)		
Documenta	tuon searched other than minimum documentation to the extent the	nat such documents are inclu	uded in the fields se	arched
Electronic d	data base consulted during the international search (name of data	hase and, where practical, s	search terms used)	
C DOCUM	AUNTE CANDIDATION TO DE OU CALLE	<u> </u>		
Category *	MENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document, with indication, where appropriate, of the	e relevant passages		Relevant to claim No.
A	WO,A,89 12032 (MANVILLE SALES C 14 December 1989 see page 5 - page 6; example 22	·		1-4
A	FR,A,2 690 438 (ISOVER SAINT-GO October 1993 see claim 1; example 2	BAIN) 29		1-4
A	WO,A,92 09536 (PAROC OY AB) 11 see claims	June 1992		1-4
C Control		Dura familia		
	ner documents are listed in the continuation of box C.	X Patent family m	icmhers are listed in	annex.
'A' docume conside 'E' earlier difiing d. 'L' documes which is citation 'O' docume other m'P' documes	nt which may throw doubts on priority claim(s) or is cited to establish the publication date of another i or other special reason (as specified) int referring to an oral disclosure, use, exhibition or	cited to understand invention "X" document of particu cannot be considere involve an inventive "Y" document of particu cannot he considere document is combine	not in conflict with the principle or the clark relevance; the clark relevance in the clark relevan	the application but cory underlying the claimed invention be considered to current is taken alone claimed invention rentive step when the re other such docu- s to a person skilled
	August 1995	Date of mailing of the	. 08. 95	rch report
Name and m	European Patent Office, P.B. 5818 Patentlaan 2 NI 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Eur. (+ 31-70) 340-3046	Authorized officer Van Bomm	nel. L	

1

INTERNATIONAL SEARCH REPORT

information on patent family members

Inten al Application No
PCT/EP 95/01843

Patent document cited in search report	Publication date		Patent family member(s)	
WO-A-8912032	14-12-89	AU-A- US-A-	3765789 5332699	05-01-90 26-07-94
FR-A-2690438	29-10-93	AU-B- BR-A- CA-A- CN-A- CZ-A- EP-A- WO-A- HU-A- JP-T- NO-A- SI-A-	4263293 9305492 2110998 1078708 9302865 0596088 9322251 67212 6508600 934725 9300218	29-11-93 11-10-94 11-11-93 24-11-93 19-10-94 11-05-94 11-11-93 28-03-95 29-09-94 20-12-93 31-12-93
WO-A-9209536	11-06-92	FI-B- AT-T- AU-A- DE-D- EP-A-	93346 117662 8908791 69107091 0558548	15-12-94 15-02-95 25-06-92 09-03-95 08-09-93